RS-2000

Magnetic Card Reader

- **Port Powered Magnetic Stripe Reader with RS232 interface**
- **Available in dual or triple track configuration**
- **Read high & low coercivity magnetic stripes (300-4000oe)**
- **Ultra compact size**
- **Track format programmable**
- **CE FCC Certified**

Card handling	Manual swipe, bi-directional
Applicable cards	For cards conforming to ISO / IEC 7811, CA DMV & AAMVA standards
Color	Pearl White
Environment	Temperature : -10°C ~ 55°C Humidity : 10 ~ 90% RH
Life	More than 500,000 passes in normal use
Consumption	Stand-by 2,5mA; Transmission 6-7 mA Max.
Read speed	5-55 ips
Read error rate	< 0.5%
Card thickness	0.25mm – 1.2mm
Rating	FCC classA, CE classB
Interface	RS232C
Weight	180 grams 6.4ozs
Dimensions	95mm (L) x 36mm (W) x 34mm (H) 3.8in (L) x 1.35in (W) x 1.50in (H)
Model Configuration	RS2000-12W: Reads Track 1 and 2 RS2000-33W: Reads Track 1, 2 and 3

Note : All specifications are subject to change without notice

SECURE-TECH

Securetech Peripherals, Inc.,
336 N. Gaffey Street 2nd Floor
San Pedro, CA 90731 U.S.A.

http://securetech-corp.com
sales@securetech-corp.com
Phone : 310-547-8501, Fax : 310-521-9600